

Wildcat+ 1280 Series



HIGH-RESOLUTION SWIR CAMERA

KEY FEATURES



HIGH-RESOLUTION SWIR IMAGING



INDUSTRY PROVEN CAMERA DESIGN



**FLEXIBLE OPTICAL MOUNT &
LENS OPTIONS**

The Wildcat+ 1280 series is based upon a state-of-the-art InGaAs photodiode array with 1280x1024 pixels and 5 μm pixel pitch. The camera offers superior, high resolution SWIR imaging capabilities, comes in a versatile and industry-proven Wildcat camera package (GenICam compliant), and offers advanced onboard image processing.

The Wildcat+ 1280 camera outputs full frame images at 120 Hz via either a CameraLink or USB3 Vision interface.

Camera Specifications	Wildcat+ 1280 CL	Wildcat+ 1280 U3V
Mechanical specifications		
Dimensions (width x height x length) [mm]	55 x 55 x 72	55 x 55 x 91.5
Weight [gr] – excluding lens	345	385
Optical interface	C-mount or M42	
Connector USB	NA	USB 3.0 type micro-B
Connector CameraLink	standard SDR	NA
Connector power	Lemo 1B.308 (unified connector)	
Connector trigger	Lemo 1B.308 (unified connector)	
Connector serial command	Lemo 1B.308 (unified connector)	
Environmental & power specifications		
Operating case temperature [°C]	From -40 to 70	
Storage temperature [°C]	From -40 to 85	
Power consumption [W]	< 7	
Power supply voltage	DC 12 V	
Shock	40g, 11ms, according to MIL-STD810G	
Vibration	5g (20 to 2000 Hz), according to MIL-STD810G	
IP rating	IP40	
Regulatory compliance	CE	
Electro-optical specifications		
Image format [pixels]	1280x1024	
Pixel pitch [µm]	5	
Detector type	InGaAs photodiode array with ROIC	
Sensor temperature stabilization	TE-cooler	
Integration type	Snapshot - global shutter	
Active area and diagonal [mm]	6.4 x 5.12 (diagonal 8.2)	
Optical fill factor	100%	
Spectral range [nm]	400 - 1700	
Quantum efficiency	~77% (typical peak value)	
Gain modes	Single gain	
Full well capacities [electrons]	160k	
Read noise [electrons]	200	
Dark current [electrons/second]	<3k	
Read out modes	IWR (< 7.5 ms) & ITR	
Pixel operability	> 99.5%	
Preconfigured exposure time range [ms]	0.5 ms & 5 ms & 7.5 ms	
Max frame rate [Hz] (full frame)	120	
Region of interest	Yes	
Min region size [pixels]	4 x 8 (step size 4 pixels in X & 8 pixels in Y)	
Max frame rate [Hz] (min region size)	> 3 kHz	
Command and control	CameraLink Base	USB3 Vision
Digital output format	CameraLink Base (16 bit)	USB3 Vision (16 bit)
Trigger	Connector: 2 trigger in & 2 trigger out - LVCMOS 3.3 V	Connector: 2 trigger in & 2 trigger out - LVCMOS 3.3 V; CameraLink trigger in
Product selector guide		
Part number	XEN-000814	XEN-000815

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE