

**SMALL, HIGH PERFORMANCE
UNCOOLED THERMAL CAMERA**

Xenics
EXOSENS GROUP

Gobi+ 640 Series



*SMALL, HIGH PERFORMANCE UNCOOLED
THERMAL CAMERA*

KEY FEATURES



COMPACT SIZE



**TEMPERATURE CALIBRATIONS FOR
THERMOGRAPHIC APPLICATIONS**



**EASY CONNECTIVITY VIA
MULTIPLE INTERFACES**

The Gobi+ 640 series is based on an uncooled microbolometer detector with a 640 x 480 pixel resolution.

The Gobi+ 640 offers frame rates up to 60 Hz and lower detector NETD options (<30 mK available upon request). The cameras come with either a CameraLink or GigE Vision interface. Gobi+ 640 is designed for use in PCB inspection, laser beam analysis and infection detection.

Camera Specifications	Gobi+ 640 CL	Gobi+ 640 GigE Gobi+ 640 GigE (9Hz)
Mechanical specifications		
Approx. dimensions (width x height x length) [mm]	49 x 49 x 62	49 x 49 x 79
Optical interface	M42 or M34 x 0.75	
Camera weight [gr]	208	263
Connector GigE	-	RJ-45
Connector CameraLink	Standard SDR	-
Connector power	Hirose HR10-7R-SA[73]	
Connector trigger	SMA	
Environmental & power specifications		
Ambient operating temperature range [°C]	From -40 to +60	
Storage temperature [°C]	From -40 to +85	
Power consumption [W]	2.9	4.6
Power supply voltage	DC 12 V	DC 12 V or PoE [Power over Ethernet]
Shock	40 g, 11 ms, MIL-STD810G/MIL-STD883J	
Vibration	5 g (20 to 2000 Hz), according to MIL-STD810G/MIL-STD883J	
IP Rating	IP 40	
Regulatory compliance	CE, RoHS	
Electro-optical specifications		
Image format [pixels]	640x480	
Pixel pitch [µm]	17	
Detector type	a-Si microbolometer	
Integration type	Rolling shutter	
Active area and diagonal [mm]	10.88 x 8.16 [13.6 diagonal]	
Detector NETD (Noise Equivalent Temperature Difference) [mK]	<50 [at 30 Hz, 300 K, F/1] [<30 mK available upon request]	
Spectral range [µm]	8-14	
Pixel operability	>99.5%	
Max frame rate [Hz] [full frame]	60	60 [or 9]
Integration time range [µs]	1 - 80	
Region of interest	Yes	
Min region size [pixels]	160 x 120	
Analog-to-Digital [ADC] [bits]	16	
Command and control	CameraLink	GigE Vision
Digital output format	16 bit base CameraLink	16 bit base GigE Vision
Trigger	In or out via SMA or CL-CC1 [configurable]	In or out via SMA [configurable] [not for 9 Hz]
Product selector guide		
Part number	XEN-000645	XEN-000646 XEN-000647 [9 Hz]

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE