

SMALL, HIGH PERFORMANCE InGaAs
CAMERA WITH GigE INTERFACE

Xenics
EXOSENS GROUP

Bobcat+ 320 Series



SMALL, HIGH PERFORMANCE InGaAs
CAMERA WITH GigE INTERFACE

KEY FEATURES



FLEXIBLE AND EASY TO USE



COMPACT AND LIGHTWEIGHT



**HIGH FRAME RATE OF UP TO
400 Hz**

The Bobcat+ 320 series is based on an in-house developed, temperature stabilised InGaAs detector with a 320 x 256 pixel resolution. The improved Bobcat+ 320 comes with two gain modes (high gain and high dynamic range) and two read out modes (IWR or ITR).

Moreover, a vSWIR version is also available. The cameras have standard on-board image correction featuring non-uniformity correction (NUC), bad pixel replacement (BPR) and automatic gain control (AGC). For more info on other image enhancement features, contact our sales department.

| Camera Specifications | Bobcat+ 320 GigE 400 | Bobcat+ 320 GigE vSWIR 400 |
|--|---|--|
| Mechanical specifications | | |
| Approximate dimensions - excluding lens [width x height x length] [mm] | 55 x 55 x 82 | |
| Weight [gr] – excluding lens | 334 | |
| Optical interface | C-mount or M42 | |
| Connector GigE | RJ-45 | |
| Connector power | Hirose HR10-7R-SA[73] | |
| Connector trigger | SMA | |
| Environmental & power specifications | | |
| Operating case temperature [°C] | From -40 to +70 Also available in temperature range 0 - 50 | |
| Storage temperature [°C] | From -45 to +85 | |
| Power consumption [W] | 4 [no TE cooler] | |
| Power supply voltage | DC 12 V | |
| Shock | IEC60068-2-27 Ed4.0; half-sine; terminal saw tooth; 50 g [11 ms] | |
| Vibration | Random: IEC60068-2-64 Ed2.0; 4.3 g [20 - 1000 Hz]. Sine: IEC60068-2-6 Ed7.0; 1 g [10 - 2000 Hz] | |
| IP rating | IP40 | |
| Regulatory compliance | CE, RoHS | |
| Electro-optical specifications | | |
| Image format [pixels] | 320 x 256 | |
| Pixel pitch [µm] | 20 | |
| Detector type | InGaAs photodiode array with CTIA ROIC | |
| Sensor temperature stabilization | TE cooler | |
| Integration type | Snapshot - global shutter | |
| Active area and diagonal [mm] | 12.864 x 5.12 [diagonal 8.2] | |
| Optical fill factor | 100% | |
| Spectral range [nm] | 900 - 1700 | 500 - 1700 |
| Quantum efficiency | ~80% (typical peak value) | |
| Gain modes | High Gain [HG] & High Dynamic Range mode [HDR] | |
| Full well capacities [electrons] | 45k [HG] & 500k [HDR] | |
| Read noise [electrons] | 120 [HD] & 500 [HDR] | |
| Dark current [electrons/second] | <1E5 [at 288K sensor temp and 150 mV reverse bias] | <2E5 [at 288K sensor temp and 150 mV reverse bias] |
| Read out modes | ITR & IWR | |
| Pixel operability | >99.5% | |
| Preconfigured exposure time range [ms] | 0.1 to 40 [HG]; 0.1 to 20 [HDR] | |
| Max frame rate [Hz] (full frame) | 400 | |
| Region of interest | Yes | |
| Min region size [pixels] | 32 x 4 [step 16 x 4] | |
| Max frame rate [Hz] (min region size) | >10000 | |
| Analog-to-Digital [ADC] [bits] | 14 | |
| Command and control | GigE Vision | |
| Digital output format | GigE Vision [16 bit] | |
| Trigger | In or out via SMA [Configurable] | |
| Product selector guide | | |
| Part number | XEN-000732 | XEN-000738 |

advancedimaging@exosens.com



exosens.com

EXOSENS
REVEAL THE INVISIBLE